a polyol,
b) a polyisocyanate,
c) a blowing agent comprising

1) from about 5 to about 50 parts by weight of a C₃ and/or C₄
alkane
and
2) from about 50 to about 95 parts by weight of cyclopentane,
and optionally
d) auxiliary additives.

12. The process of Claim 11 in which c) 1) is n-butane.

33. The process of Claim 1 in which c) 1) is isobutane.

74. The process of Claim 11 in which c) further includes from about 0.5 to about 4 parts by weight of water.

The process of Claim 11 in which c) further includes from about 1.5 to about 3 parts by weight of water.

16. The process of Claim 14 in which a) includes from about 5 to about 80 parts by weight of an aromatic amine initiated polyol.

- 17. The process of Claim 11 in which a) includes from about 5 to about 80 parts by weight of an aromatic amine initiated polyol.
- 18. The process of Claim 11 in which a) includes from about 20 to about 65 parts by weight of an aromatic amine initiated polyol.
 - 19. A blowing agent composition domprising,
 - a) from about 5 to about 50 parts by weight of a C₃ and/or C₄ alkane and
 - b) from about 50 to about 95 parts by weight of cyclopentane.

Gwb 192> -20. The process of Claim 19 in which a) is n-butane and/or isobutane.

21. A rigid polyurethane foam plastic produced by the process of Claim 11. - -

Mo4805